

000000010/F/USA  
Approval Date: 11/28/2001  
Print Date: 07/06/2004  
Page: 1/6



---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: KODAK Alkaline Battery KC

Catalog Number(s): See last page for catalog number(s).

Manufacturer/Supplier: EASTMAN KODAK COMPANY, Rochester, New York 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151

For National Battery Poison Control Center, call: 202-625-3333

For other information or to request an MSDS, call (800) 242-2424.

Synonym(s): M-0010.000

Primary Application: Cassette players, radios, toys, flashlights

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Weight % - Component - (CAS Registry No.)

35-40	Manganese dioxide (001313-13-9)
15-20	Zinc Powder (007440-66-6)
5-10	Water (007732-18-5)
5-10	Potassium hydroxide (001310-58-3)
1-5	Graphite (007782-42-5)

15-20	Steel Casing (not applicable)
1-5 1-	Paper (not applicable)
5 1-5	Alloy Brassy (not applicable)
< 1	Plastic (not applicable)
	Metalized plastic label (not applicable)

Weight % listed is based on approximate percent of the average weight of the battery (70 grams).

The components in this section may only represent a hazard if the integrity of the battery is compromised.

---

### 3. HAZARDS IDENTIFICATION

CONTAINS: Potassium hydroxide (001310-58-3), Manganese dioxide (001313-13-9), Graphite (007782-42-5)

WARNING!

HARMFUL IF SWALLOWED

MAY VENT, LEAK AND/OR EXPLODE IF OPENED, RECHARGED, CONNECTED IMPROPERLY, OR EXPOSED TO FIRE OR HIGH TEMPERATURES.

VAPORS/FUMES FROM DAMAGED BATTERIES MAY CAUSE RESPIRATORY TRACT IRRITATION

DAMAGED BATTERIES MAY CAUSE SKIN AND EYE BURNS

---

[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS

MATERIAL SAFETY DATA SHEET

000000010/F/USA

Approval Date: 11/28/2001

Print Date: 07/06/2004

Page: 2/6

---

4. FIRST-AID MEASURES

Note: The routine handling and use of intact, non-damaged batteries is not expected to result in situations that require first-aid measures. If battery is damaged due to opening, cutting, crushing, overheating, improper installation, exposure to fire or high temperatures, or recharging, battery contents may be released.

Inhalation: If vapors or fumes from vented or leaking battery are irritating to respiratory tract, move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.

Eyes: In case of contact with battery contents (liquid or metal), immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin: In case of contact with battery contents (liquid or metal), immediately remove metal fragments and flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes. Get medical attention immediately.

Ingestion: Call a physician or poison control center immediately for any actual or suspected ingestion. All batteries may be harmful if swallowed. Do NOT induce vomiting. Batteries may lodge in the throat or digestive tract and fragment. If battery was leaking or was chewed, rinse mouth thoroughly with water.

---

5. FIRE FIGHTING MEASURES

Extinguishing Media: Use appropriate agent for adjacent fire.

Special Fire-Fighting Procedures: Fire or excessive heat may produce hazardous decomposition products. Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: Oxides of manganese, oxides of zinc

Unusual Fire and Explosion Hazards: Fire or high temperatures may cause battery to vent and/or explode or leak hazardous vapors. Damaged or opened batteries can result in rapid heating and the release of hazardous vapors.

---

6. ACCIDENTAL RELEASE MEASURES

Not applicable

---

[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS

[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS

MATERIAL SAFETY DATA SHEET

000000010/F/USA

Approval Date: 11/28/2001

Print Date: 07/06/2004

Page: 3/6

-----

7. HANDLING AND STORAGE

Personal Precautionary Measures: If battery has been damaged, do not breathe fumes or vapors. Do not get battery contents in eyes, on skin, on clothing. Wash thoroughly after handling.

Prevention of Fire and Explosion: DO NOT DISASSEMBLE. Keep away from heat and flame. DO NOT RECHARGE. Charging may result in electrolyte leakage and/or explosion. Avoid the use of old and new batteries or batteries of varying sizes and types in the same battery assembly. The batteries electrical characteristics and capabilities may vary and damage may result to the batteries or electrical equipment. Avoid encasing in airtight compartments. Flammable hydrogen gas, normally generated, can form explosive mixtures. Provisions for venting must be provided. Avoid reversing polarity within a device or a battery assembly. To do so may cause leakage and/or explosion.

Storage: Store in cool, dry place. Protect from direct sunlight. Storage above 21°C (70°F) may affect product quality. Do not store in a manner that allows terminals to short circuit. Extended short circuiting creates high temperatures in the battery. High temperatures can cause leakage and/or explosion. Short circuiting may reduce battery service life.

-----

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

ACGIH Threshold Limit Value (TLV):

Potassium hydroxide: 2 mg/m3 Ceiling

Graphite: 2 mg/m3 TWA

Manganese dioxide: 0.2 mg/m3 TWA as manganese

OSHA (USA) Permissible Exposure Limit (PEL - 1971 Table Z-1 Values):

Graphite: 15 mg/m3 TWA Total dust; 5 mg/m3 TWA Respirable fraction

Manganese dioxide: 5 mg/m3 TWA as manganese

Ventilation: Supplemental ventilation may be needed in special circumstances to control fumes/vapors to an acceptable level.

Respiratory Protection: None should be needed.

Eye Protection: When handling a damaged battery, wear safety glasses with side shields (or goggles).

Skin Protection: When handling a damaged battery, wear impervious gloves.

-----

[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS

Recommended Decontamination Facilities: Washing facilities

[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS

MATERIAL SAFETY DATA SHEET

000000010/F/USA  
Approval Date: 11/28/2001

Print Date: 07/06/2004  
Page: 4/6

-----  
9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Solid  
Color: Not applicable  
Odor: Odorless  
Specific Gravity (water = 1): Not applicable  
Vapor Pressure: Negligible  
Vapor Density (Air = 1): Not applicable  
Volatile Fraction by Weight: Not applicable  
Melting Point: Not applicable  
Solubility in Water: Insoluble  
pH: Not applicable  
Flash Point: Not applicable

-----  
10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use.

Incompatibility: None with common materials and contaminants with which the material may reasonably come into contact.

Hazardous Polymerization: Will not occur.

-----  
11. TOXICOLOGICAL INFORMATION

Effects of Exposure:

General: Since the materials in this battery are sealed in the battery case, the potential for exposure to the components of the battery is negligible when the battery is used as directed. However, technical or electrical abuse of the battery may result in the release of battery contents.

Inhalation: Expected to be a low hazard for recommended handling.  
Vapors/fumes from damaged batteries may cause respiratory tract irritation.

Eyes: Contact with electrolyte (liquid) causes burns. Contact with metal fragments may cause burns or mechanical injury.

Skin: Contact with electrolyte (liquid) causes burns. Contact with metal fragments may cause burns or mechanical injury.

Ingestion: All batteries may be harmful if swallowed. May cause burns of the gastrointestinal tract.

Note to Physicians: Battery ingestions should not be managed in the same way as other small metallic object ingestions, eg., coins. The position and integrity of the battery in the gastrointestinal tract should be assessed and monitored by x-ray. Leaking batteries may cause necrosis and tissue damage. Most batteries smaller than 22-25 mm in diameter will pass safely through the gut. Larger batteries or batteries that lodge in the gastrointestinal tract may have to be removed endoscopically or surgically.

-----  
[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS

MATERIAL SAFETY DATA SHEET

000000010/F/USA  
Approval Date: 11/28/2001

Print Date: 07/06/2004  
Page: 5/6

-----  
12. ECOLOGICAL INFORMATION

This material has not been tested for environmental effects.

-----  
13. DISPOSAL CONSIDERATIONS

DO NOT INCINERATE or expose to fire. Discharge, treatment, or disposal may be subject to national, state, or local laws.

-----  
14. TRANSPORT INFORMATION

- For transportation information regarding this product call the Kodak Worldwide Transportation Hazmat Hot Line: (585) 722-2400 between 8 a.m. and 5 p.m. (Eastern Standard Time), Monday through Friday.

-----  
15. REGULATORY INFORMATION

- Material(s) known to the State of California to cause cancer: None
- Material(s) known to the State of California to cause adverse reproductive effects: None
  
- Carcinogenicity Classification (components present at 0.1% or more):
  - International Agency for Research on Cancer (IARC): None
  - American Conference of Governmental Industrial Hygienists (ACGIH): None
  - National Toxicology Program (NTP): None
  - Occupational Safety and Health Administration (OSHA): None
  
- Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: Not applicable

MATERIAL SAFETY DATA SHEET

000000010/F/USA  
Approval Date: 11/28/2001

Print Date: 07/06/2004  
Page: 6/6

-----  
16. OTHER INFORMATION

Keep out of reach of children. If swallowed, seek medical advice.

-----  
The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.  
-----

Catalog Number(s):

119 1048 - KC  
121 2810 - KC-S6  
125 5066 - KC-N24  
126 2880 - KC-2  
129 9130 - KC-B234  
133 1776 - KC-N20  
139 0921 - KC  
151 2029 - KC-B260  
197 1134 - KC-4CLAM  
368 3968 - KC-S8  
511 3238 - KC-2  
511 8658 - KC-S4  
527 7694 - KC-2  
527 7744 - KC-2  
802 6745 - KC-S12  
809 6745 - KC-12  
813 7549 - KC-2  
825 5028 - KC-2  
844 8946 - KC-S6  
852 6931 - KC-2  
869 6759 - KC-S8  
873 4519 - KC-N12  
873 4519 - KC-12 Intermediate Bulk  
874 6901 - KC-S6  
875 8575 - KC-2  
877 1099 - KD-S-4  
884 4367 - KC-S12  
884 6246 - KC  
899 0491 - KC-S6

[WWW.POINTERAVIONICS.COM](http://WWW.POINTERAVIONICS.COM)

C2020 / 2020 BATTERY PACK FOR POINTER EMERGENCY LOCATOR  
TRANSMITTERS